HIMALAYAN POWER MACHINE MFG. CO. Part of Khasra No. 51 and 52 Ka, Village Kuanwala, Haridwar Road, Dehradun, Uttarakhand – 248001

Phone No.: +91-9412052496

Email: hpmgenset@gmail.com

Specfication Sheet For Model GE 1400 R/RS



Generator	Model Name	GE - 1400 R / RS
	Special Highlight	<ul> <li>India's Lightest &amp; Most Fuel Efficient 1.2 KVA Genset Can Also Runs On LPG Cylinder &amp; Produce Electricity At Most Economical Price.</li> </ul>
	Application	<ul> <li>For home &amp; shop use. For all low &amp; middle income people in power deficit state, where power cut is for more than 12 hrs. Can charge inverter battery along with other house load.</li> <li>Run's water pump, refrigerator, TV, Cooler Etc. Household appliances.</li> <li>Due to light weight, ideal for field jobs and mobile applications, picnic camps applications.</li> </ul>
	*Max AC. Output VA	1250
	*Rated AC. Output VA	1000
	Rated Current Amps	4.4
	NFB Amps	4.5
	AC. Voltage at Rated Load	220 Volts ± 10 Volt 50 Hz, Single Phase
	AC. Voltage at No Load	250 Volts ± 5 Volt
Alternator	#Alternator Max. Current Capacity	12 Amps.
	Alternator	Brushless, Rare Earth Magnetic Rotor, THD 5 %, Pure Sine Wave
Eng ine	Model	HM156P

HIMALAYAN POWER MACHINE MFG. CO.

HIMALAYAN FUWER WACHINE IN COMMERCIAL PART OF Khasra No. 51 and 52 Ka, Village Kuanwala, Haridwar Road, Dehradun,

Uttarakhand - 248001

Phone No.: +91-9412052496

Email: hpmgenset@gmail.com

	Туре	OHV25°Inclined, single cylinder, 4 strokes, S.I, Forced air cooling	
	Maximum Power	3.0 hp @ 3600rpm	
	Bore x Stroke	56×40 mm	
	Displacement	98cc	
	Starting System	Recoil Start & Self Start	
	Fuel	Petrol	
	Fuel Tank Capacity	Petrol -7.5 Ltr.	
	Fuel Consumption	0.60 ltr/hr, (At rated Load)	
	Lube. Oil Capacity	400 ml.	
	Lubricating Oil Consumption	6.5gm./Kw./hr.	
	Continues Running (With One Filling)	12.5 Hrs.	
	Sound level (Db) (from 1 meter)	<86Db	
Panel & Other Standard Features	Voltmeter	Yes (Analogue)	
	Digital Hour Meter	No	
	Oil Alert System	Yes	
	LPG/ Gas Fuel Compatibility	Yes (Optional)	
	AMF Panel Auto & Remote Start Compatibility	No	
	Fuel Level Gauge	Yes	
	Overload Protection (NFB)	Yes	
	Costar Wheels	Optional	
Size & Weight	Gross weight-KG (With Battery)	32.5 KG / 36 KG	
	Dimension L x W x H (mm)	500x365x460 mm	
	Battery Dimension in (mm)	146 x 60 x 130 mm	
Specifications are for reference only, Because of continuous improvements and up-gradation by our R&D team. This specifications can change without any prior intimation			